

FIBOX ARCA Electrical Enclosure

ARCA403015

HIGH PERFORMANCE POLYCARBONATE | IP66 IK10

400H x 300W x 150D

ACCESSORIES:

| Part Number | Description |
|------------------|---|
| IDS ARCA 4030 | Aluminium Inner Door Set 385mmH x 285mmW x 35mmD; RAL7035 |
| DRS ARCA 403015* | Galvanised Steel DIN Rail Frame Set 385mmH x 285mmW x 35mm |
| PMK ARCA 30 | Stainless Steel Pole Mounting Kit for Ø100-300mm Pole 385mmH x 285mmW x 35mmD |
| DSP ARCA VRS | Galvanised Steel Door Stopper ARCA; Vertical; Right; Small 15mmH x 104mmW x 16mmD |
| DSP ARCA VLS | Galvanised Steel Door Stopper ARCA; Vertical; Left; Small 15mmH x 104mmW x 16mmD |

*2 rows x 11 modules for size 400H x 300W x 150D ARCA Enclosure

PARAMETERS:

| | |
|--|-----------------------|
| Electrical Insulation: | Fully Insulated |
| Halogen Free (DIN/VDE 0472, Part 815): | Yes |
| UV Resistance: | UL 746C |
| Flammability Rating: | UL 94 5VA |
| Glow Wire Test (IEC 60695)°C: | 960°C |
| NEMA Class: | NEMA 1, 4, 4X, 12, 13 |
| Temperature °C (short term): | -40...+120°C |
| Temperature °C (continuous term): | -40...+80°C |

CERTIFICATES:

Certificate FI 42298.