

IP33 Outdoor Field Cabinet IP-2X24U6560-LVR-GRN

STEEL | SINGLE DOOR | IP33

2 x 24U (48U) 19" - 1300W x 600D
Louvred

IP Enclosures FC Range of IP33 19" Field Data Rack Cabinets are designed for heavy duty outdoor applications to house sensitive data network and electrical equipment in harsh environments. They are suitable for a variety of outdoor applications including road and rail transport management systems and general data and network infrastructure applications.

Protection: Complies with IP33 IK10, NEMA 4 (Louvred)

Standard: IEC62208, IEC/EN/AS60529, EIA-310-D  

Rack Unit Size: 2 x 24U (48U)

Material:

- Body and Plinth: 2.0mm galvanised steel sheet
- Door: 2.0mm galvanised steel sheet
- 19" Data Rack Rails: 1.5mm galvanised steel sheet
- Gland Plate: 3.0mm aluminium
- Enclosure Seal: Polyurethane

Body: The robust monoblock body is fabricated using 2.0mm galvanised steel sheet. The body is fitted with rain hood/sunshield and plinth. Flat face sealing surfaces are provided to increase seal life. A 3mm galvanised steel split gland plate is also incorporated into the bottom face.

Base: The base is 150mm high and fabricated using a 2.0mm galvanised steel sheet.

Door: The door is fabricated using 2.0mm galvanised steel sheet and is designed to provide flush recessed mounting to prevent vandalism and unauthorised access. The door incorporates concealed removable hinges with captive pins. It is designed for a 110° opening and is provided with heavy duty door stays.

19" Data Rack Rails: Front and rear 19" data rack rails are fabricated from 1.5mm galvanised steel sheet.

Seal: A high quality full perimeter Polyurethane foamed in place (FIP) seal provides excellent sealing over a long life.

Locks: 8mm Square Grade 316 Stainless Steel.

Surface Treatment: UL approved polyester powder-coated with a smooth gloss finish, 80-120 micron average thickness, providing excellent exterior durability and color retention. Colour: RAL 6005 Moss Green.

