

AC Air Conditioner

IP-ACIWM400.433.0X

304 STAINLESS STEEL | INDOOR | WALL MOUNTED | IP54

4000 Watt

IP Enclosures Grade 304 stainless steel vertical-mount compact IP54 Air Conditioners are specifically designed for the cooling needs of indoor electrical cabinets. Made in Italy, these air conditioners are corrosion-resistant to harsher environments. They are optimised for door or side-panel mounting and have been designed for high efficiency and low maintenance.

Protection: IP54

Standards (& Conformities): AS/NZS 60335.2.40:2019, AS/NZS 60335.1:2020.





Temperature Control Type: Digital thermostat with alarm; Door interlock; RS485 Interface.

Casing: Galvanised steel sheet.

Cover: Grade 304 stainless steel.

Mounting: Maximum 5Nm for M6 screws.



MOUNTING CUT-OUT




Figure 01






Figure 02

OPTIONAL DUCTING SYSTEM FOR AIR CONDITIONER:


1. **IP-FD400** - 172Hx312Wx87D Internal Flow Diverter; Colour RAL7035 Grey
2. **IP-ACFMV400** - Flow Diverter Adapter suitable for 2800W & 3800W Indoor Air Conditioners
3. **IP-ACDSL1000** - Flat Duct 1000mm suitable for Wall Mounted & Roof Mounted Air Conditioners
4. **IP-ACDSC** - Flat Duct Connector suitable for Wall Mounted & Roof Mounted Air Conditioners
5. **IP-ACDS90** - 90° Duct Bend suitable for Wall Mounted & Roof Mounted Air Conditioners
6. **IP-ACDBV400** - Duct Booster Fan suitable for 2800W & 3800W Indoor Air Conditioners



FRONT VIEW



RIGHT SIDE VIEW



BOTTOM VIEW



AC Air Conditioner

IP-ACIWM400.433.0X

304 STAINLESS STEEL | INDOOR | WALL MOUNTED | IP54

4000 Watt

Features	Unit	IP-ACIWM400.433.0X
Power supply	V/Hz	400V/3ph/50 - 460/3ph/60
Dimensions HxWxD	mm	1500x400x255
Cooling capacity EN14511 A35-A35	W	3800/3980
Cooling capacity EN14511 A35-A50	W	2800/3160
Absorbed electric power EN14511 A35-A35	W	2200/2320
Absorbed electric power EN14511 A35-A50	W	2600/2750
Rated current	A	2.7/3.0
Motor circuit breaker / Delayed pre fuse (advised)	A	16
Electrical connection	-	Quick connector
Air flow rate (free blow) enclosure	m³/h	860/950
Operating temperature (ambient)	°C (°F)	+20 / +55 (+68 / +131) +20 / +50 (+68 / +122)
Operating temperature (enclosure)	°C (°F)	+20 / +45 (+68 / +113)
Temperature controller (factory set at 35°C)	-	Digital thermostat with alarm; Door interlock; RS485 Interface
Refrigerant / charge	- g	R134a 1000
Condensate management	-	Condensate evaporator with safety overflow
Protection degree EN60529/1 (ambient side)	-	IP34
Protection degree EN60529/1 (enclosure side)	-	IP54
Casing	-	Galvanised steel sheet
Cover	-	Grade 304 stainless steel
Package dimensions HxWxD	mm	1610x435x290
Weight (with packaging)	Kg	75 (78)
Conformity / Certifications	-	AS/NZS 60335.2.40:2019, AS/NZS 60335.1:2020 

ACCESSORIES:

Part Number	Description
IP-FD400	172Hx312Wx87D Internal Flow Diverter; Colour RAL7035 Grey
IP-ACIWM300400-FILTER	411Hx337Wx6D External Filter; Polyurethane Filter Mat
DUCTING SYSTEM ACCESSORIES for A/C	Refer to Page 1; Figure 02 Diagram

CERTIFICATES:

IEC 60335-2-40 Safety of household and similar electrical appliances Part 2-40: Particular requirements for electrical heat pumps, air conditioners and dehumidifiers. (IEC 60335-2-40:2018 in conjunction with IEC 60335-1:2010, AMD1:2013, AMD2:2016). Attachment to Test Report IEC 60335-1 (Australia / New Zealand) National Differences. Differences According to AS/NZS 60335.1:2011 + A1:2012 + A2:2014 + A3:2015 + A4:2017 + A5:2019. Certificate RA-64 ELDO 2020.

Products are manufactured to Quality, Safety and Environmental Standards.